

**SIGMZAM FINISH GLOSS**

Version 1

Print Date Dec 2002

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING****Product information****Trade name** 0617 SIGMAZAM FINISH GLOSS**Company** : Sigma Paints Saudi Arabia Ltd  
PO Box 7509  
Dammam 31472**Telephone** : 9663 8473100**Telefax** : 9663 8471734**Emergency telephone number** : +9663 8572394**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Components	CAS-No.	Symbol(s):	R-phrases)	Concentration
TOLUENE	108-88-3	F, Xn	R11, R20	2.50 - 10.00%
XYLENE	1330-20-7	Xn	R10, R20/21, R38	10.00 - 25.00%
ETHYL BENZENE	100-41-4	F, Xn	R11, R20	2.50 - 10.00%
LEAD COMPOUNDS WITH THE EXCEPTION OF THOSE SPECIFIED ELSEWHERE IN THIS ANNEX	68603-83-8	T, N	R61, R20/22, R33, R50/53, R62	0.00 - 2.50%

**3. HAZARDS IDENTIFICATION****Harmful****Hazardous components :**

XYLENE

**R-phrase(s) :**

FLAMMABLE.

HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.

**S-phrase(s) :**

Do not breathe spray.

Wear suitable protective clothing and gloves.

In case of insufficient ventilation, wear suitable respiratory equipment.

**4. FIRST AID MEASURES**

- General advice** : When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.
- Eye contact** : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Remove contact lenses. Seek medical advice.
- Skin contact** : Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Inhalation** : Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

**SIGMZAM FINISH SEMI GLOSS**

Version 1

Print Date Dec 2002

**Ingestion** : If accidentally swallowed obtain immediate medical attention. Keep at rest. Do not induce vomiting.

**5. FIRE-FIGHTING MEASURES**

**Specific hazards during fire fighting** : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

**Special protective equipment for fire-fighters** : In the event of fire, wear self-contained breathing apparatus.

**Suitable extinguishing media** : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Keep containers and surroundings cool with water spray.

**Extinguishing media which must not be used for safety reasons** : Do NOT use water jet.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** : Use personal protective equipment. Ventilate the area. Refer to protective measures listed in sections 7 and 8. Wear respiratory protection. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Remove all sources of ignition.

**Environmental precautions** : Try to prevent the material from entering drains or water courses. If the product contaminates rivers and lakes or drains inform respective authorities.

**Methods for cleaning up** : Clean with detergents. Avoid solvents. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**Additional advice** : Refer to section 15 for specific national regulation.

**7. HANDLING AND STORAGE**

**Handling**

**Safe handling advice** : Avoid exceeding of the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8.

**Advice on protection against fire and explosion** : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. No smoking. The accumulation of contaminated rags and dry overspray, particularly in spray booth filters, may result in spontaneous combustion. Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

**SIGMZAM FINISH GLOSS**

Version 1

Print Date Dec 2002

**Storage**

**Requirements for storage areas and containers** : Observe label precautions. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store between 5 and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Electrical installations / working materials must comply with the technological safety standards. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations (see section 15).

**Advice on common storage** : Keep away from oxidising agents and strongly acid or alkaline materials.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Minimum ventilated air quantity for 1 liter of product**

**TO REACH 10 % LEL** : 83 m<sup>3</sup>/l

**Components with workplace control parameters**

Components	CAS-No.	Value [mg/m <sup>3</sup> ]	Value [ppm]	Basis
TOLUENE	108-88-3	150.00	40.00	MAC (NL) MAC TGG
XYLENE <i>can be absorbed through skin can be absorbed through skin</i>	1330-20-7	210.00 221.00 221.00	50.00 50.00 100.00	MAC (NL) MAC TGG EU ELV TWA EU ELV STEL
ETHYL BENZENE <i>can be absorbed through skin can be absorbed through skin</i>	100-41-4	215.00 442.00 442.00	50.00 100.00 200.00	MAC (NL) MAC TGG EU ELV TWA EU ELV STEL
CALCIUM CARBONATE	1317-65-3	10.00		MAC (NL) MAC TGG
MAGNESIUM SILICATE	14807-96-6	2.00		MAC (NL) MAC TGG

**Personal protective equipment**

**Personal protection advice** : Use personal protective equipment. Ventilate the area. Refer to protective measures listed in sections 7 and 8. Wear respiratory protection. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Remove all sources of ignition.

**Respiratory protection** : Apply technical measures to comply with the occupational exposure limits. This should be achieved by a good general extraction and "if practically feasible" by the use of local exhaust ventilation. If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.

**Hand protection** : For prolonged or repeated contact use protective gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact.

**Eye protection** : Chemical resistant goggles must be worn.

**SIGMZAM FINISH GLOSS**

Version 1

Print Date Dec 2002

**Skin and body protection** : Personnel should wear protective clothing. Skin should be washed after contact. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire. Workers should wear antistatic footwear.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Form** : viscous

**Colour** : various

**Odour** : mild aromatic

**Flash point** : 25 °C

**Autoignition temperature** : > 480 °C

**Lower explosion limit** : 1.03 %(V)

**Density** : 1.3 - 1.6 g/cm<sup>3</sup>

**Water solubility** : immiscible

**Viscosity, dynamic** : 800 mPa.s at 23 °C

**10. STABILITY AND REACTIVITY**

**Conditions to avoid** : Avoid temperatures above 60°C, direct sunlight and contact with sources of heat.

**Hazardous reactions** : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**Hazardous decomposition products** : In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

**11. TOXICOLOGICAL INFORMATION**

**Acute oral toxicity** : May cause nausea, abdominal spasms and irritation of the mucous membranes.

**Acute inhalation toxicity** : Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects. Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

**Skin irritation** : Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in desiccation of the skin. The product may be absorbed through the skin.

**Eye contact** : The liquid splashed in the eyes may cause irritation and reversible damage.

**Further information** : There is no data available for this product.

**12. ECOLOGICAL INFORMATION**

**Further information** : There is no data available for this product.

**SIGMZAM FINISH GLOSS**

Version 1

Print Date Dec 2002

**13. DISPOSAL CONSIDERATIONS**

**Product** : The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

**14. TRANSPORT INFORMATION**

**ADR** : Class : 3 / 31c  
UN-No : 1263  
ADR/RID-Labels : 3  
Limited Quantities: Max. per inner pack.: 5.00 L - Max. per outer pack.: 45.00 L  
Proper shipping name : PAINT

**IMDG** : Class : 3.3  
UN-No : 1263  
IMDG labels : 3  
EmS : 3-05  
MFAG : 310  
IMDG Page : 3372  
Packaging group : III  
Proper shipping name : PAINT

**IATA\_C** : Class : 3, Sub-risks :  
UN-No : 1263  
Packaging group : III  
Proper shipping name : PAINT

**Note** : ADR : Packagings smaller or equal to 450 l, transport according to section E of marginal 2301.

**15. REGULATORY INFORMATION**

**Remarks** : *A hard copy of the label is placed in section 3*

**Hazardous components which must be listed on the label:**

- XYLENE

**Symbol(s)** : Xn Harmful

**R-phrased(s)** : R10 Flammable.  
R20/21 Harmful by inhalation and in contact with skin.

**S-phrased(s)** : S23 Do not breathe spray.  
S36/37 Wear suitable protective clothing and gloves.  
S38 In case of insufficient ventilation, wear suitable respiratory equipment.

**VOC** : 380.4 g/l  
Method: Calculated

**National legislation**

**Vlarem** : Vlarem 2A

**SIGMZAM FINISH GLOSS**

Version 1

Print Date Dec 2002

**CPR Classification** : K3 Xn

**NER Classification** : NER Class O.1: 0.0 %(m)  
NER Class O.2: 25.1 %(m)  
NER Class O.3: 0.6 %(m)

**16. OTHER INFORMATION****Explanation of R-phrases mentioned in section 2**

TOLUENE	R11	Highly flammable.
	R20	Harmful by inhalation.
XYLENE	R10	Flammable.
	R20/21	Harmful by inhalation and in contact with skin.
	R38	Irritating to skin.
ETHYL BENZENE	R11	Highly flammable.
	R20	Harmful by inhalation.
LEAD COMPOUNDS WITH THE EXCEPTION OF THOSE SPECIFIED ELSEWHERE IN THIS ANNEX	R61	May cause harm to the unborn child.
	R20/22	Harmful by inhalation and if swallowed.
	R33	Danger of cumulative effects.
	R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R62	Possible risk of impaired fertility.

Changes since the last version will be highlighted in the margin. This version replaces all previous versions.

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation at the date of issue. The company reserves the right to modify data without notice. Any change in data will normally be followed by issue of a new safety data sheet. The user should check the date of issue and if more than 12 months have elapsed, then the data should only be used after checking with our nearest sales office to establish that they are still valid. . As the specific conditions of use of the product are outside the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. None of the information contained in this safety data sheet can be constructed as a guarantee with regard to the properties of the product described. No liability can be accepted on the basis of this safety data sheet.

After all component(s) stated on the relevant Technical Data Sheet have been mixed the safety precautions mentioned on each of the component(s) safety data sheets and labels should be used in assessing the safety precautions of the mixed product.

For further information see technical data sheet number: 0617